

Technical data / Fish skinning machines

machine model	cutting width	cutting speed	blade gap (infinitely adjustable)	maximum throughput height	apply length on infeed conveyor	overall dimension W x H x D	weight	motor performance	electrical connection	water connection	approx. water consumption	compressed air
	mm	m/min	mm	mm	mm	mm	kg	kW			l/h	bar
Cortex CBF 495	430	19	0 - 5	70	400	800 x 1190 x 1660	240	0.75			200	-
Cortex CBF 495 SALMON	430 ^⑤	19	0 - 5	70	400	800 x 1190 x 1660	250	0.75			200	6 - 10
Skinex SB 495	430	19	0 - 5	70	400	800 x 1190 x 1660	240	0.75			200	-
Skinex QS 888	2X 200	29 ^②	0 - 2	40	540	800 x 1190 x 1200/1620 ^⑤	220/240 ^⑤	1.1	① 3 AC - 400 / 230 V - 50 (60) Hz	G 1/8" internal thread	200	-
Cortex CF 460	430	19	0 - 4	-	-	740 x 960 x 630	150	0.75			100	-
Skinex S 460	430	29	0 - 4	-	-	740 x 960 x 630	160	0.75			100	-
Cortex CF 420	430	19	0 - 3.5	-	-	700 x 420 x 500 (700 x 950 x 600) ^④	80 (95) ^④	0.75			80	-
Skinex S 420	430	29	0 - 3.5	-	-	700 x 420 x 500 (700 x 950 x 600) ^④	80 (95) ^④	0.75			80	-
Cortex CF 300 COUNTERBOY	280	19	0 - 3.5	-	-	560 x 320 x 400 (560 x 950 x 500) ^④	50 (65) ^④	0.25			50	-

① other voltages available upon request

② infeed conveyor belt speed

③ 2 lane version available

④ with underframe

⑤ without/with output conveyor

NOCK Maschinenbau GmbH
 Industriestrasse 14
 77948 Friesenheim
 GERMANY

Tel: +49 (0) 7821-99 78 16
 Fax: +49 (0) 7821-99 78 18
 E-mail: info@nock-gmbh.com
 www.nock-gmbh.com